Honeywell

Dolphin 99EX

Mobile Computer

Purpose built for transportation and logistics applications, Honeywell's Dolphin[®] 99EX mobile computer provides user-friendly ergonomics, cutting-edge wireless technology, multi-functional data capture and extreme durability for front-line workers operating in a variety of locations ranging from loading docks to residential doorsteps.

The reliable and intuitive Dolphin 99EX delivers an outstanding feature set that enables improved productivity for mobile workers. Integrated Shift-PLUS[™] technology provides all day battery life, minimizing the time and expense incurred when batteries need to be charged or replaced. The Dolphin 99EX is IP67-rated and can withstand multiple 6 feet (1.8 meters) drops to concrete, ensuring years of trouble-free operation.

The 99EX features the latest in wireless technology, including a softwaredefinable radio that allows on-the-fly switching between GSM and CDMA networks, leading to improved network coverage and lower costs related to device provisioning and deployment. Additionally, built-in Wi-Fi provides workers with access to critical data using the new, lightning fast 802.11n standard while still supporting legacy a/b/g protocols.

Integrated motion, light and proximity sensors help conserve battery life and improve ease of use by automatically optimizing the offering for the current environment. Similarly, multiple keypad options are available to ensure that the device is configured to meet diverse data input needs. With additional features such as an ultra-bright 3.7 inch display that can be read, even in direct sunlight, the Dolphin 99EX offers superior usability.

Designed with input from leading companies in the transportation and logistics sector, Honeywell's Dolphin 99EX mobile computer provides a rugged solution that increases productivity by connecting enterprises, front-line workers and customers using real-time wireless communication.



Features

- **Superior Durability:** Incorporates an IP67-rated design that withstands multiple 6 feet drops to concrete and 2,000 1 meter tumbles, resulting in a lower total cost of ownership for enterprises
- Shift-PLUS Power Management: Enhances productivity by providing full shift battery life, eliminating the need for employees to carry spare batteries or chargers
- Adaptus[®] Imaging Technology 6.0: Enables multifunctional data capture by providing fast scanning of linear and 2D bar codes with excellent motion tolerance, as well as seamless image capture through use of an integrated color camera
- Fast and Reliable Wireless Connectivity: Delivers full wireless coverage for applications inside and outside of the four walls, allowing real-time access to critical data
- Optimal Combination of Performance and Usability: Improves ease of use and worker efficiency with a large outdoor-viewable screen, multiple keypad options, a super fast CPU and smart sensors
- Optional Remote MasterMind[®] Software Package: Extends mobile workforce capabilities and reduces total cost of ownership by providing a turnkey remote device management solution
- Optional Service Made Simple[™] Service Plans: Offers comprehensive, hassle-free protection on the device investment for up to five years after purchase

Dolphin 99EX Technical Specifications

Mechanical/Environmental	
Dimensions	8.5 [°] L x 2.7 [°] W (keypad) x 1.5 [°] (standard battery)/1.8 [°] (extended battery) 215 mm L x 69 mm W (keypad) x 39 mm (standard battery)/45mm (extended battery)
Weight	Standard battery – 520g (18.3 oz.); Extended battery – 570g (20.1 oz.)
Operating Temperature	-4° to 122°F (-20° to 50°C)
Storage Temperature	-13° to 158°F (-25° to 70°C)
Humidity	95% humidity, non-condensing
Drop	Withstands multiple 6' (1.8m) drops to concrete, all axis, and across operating temperature range
Tumble	Exceeds 2,000 (1m) tumbles per IEC 60068-2-32 specification
Environmental Sealing	Independently certified to meet IP67 standards for moisture and particle resistance
ESD	Air: ±15 KV; Contact: ±8 KV
System Architecture	
Processor	Texas Instruments® OMAP3715 1.0GHz processor
Operating System	Microsoft® Windows Embedded Handheld 6.5 Professional and Classic
Memory	1GB discrete NAND flash x 256 MB RAM
Display	Chemically strengthened 3.7" transflective active matrix glass display, VGA (480x640), 333 nits
Touch Panel	Industrial touch panel with resistive touch and support for finger touch and stylus
Keypad	Backlit 55-key alphanumeric, 43-key alpha shifted numeric, 34-key numeric shifted alpha (phone or calculator style)
Audio	Speaker, HAC compliant receiver, microphone
Camera	3.1 megapixel camera with Automated Camera Control (ACC). Features include automated picture profiles, camera Application Programming Interface (API), cooperational use of camera and imager, and flashlight utility
I/O Ports	RS-232/USB 2.0/audio out/charging connector, integrated IrDA port with support for SIR mode
Storage Expansion	MicroSD card (support for up to 32GB)
Battery	Standard – Li-ion, 3.7V, 3060mAh; Extended – Li-ion, 3.7V, 5000mAh
Battery Life	Standard/Extended: 9 hours/15.5 hours (scanning and sending data over WLAN every 9 seconds) Standard/Extended: 8 hours/14.75 hours (scanning and sending data over WWAN every 15 seconds, GPS continuously receiving information)
Imager/Scanner	N5600/5603 Standard range (SR), Extended range (ER), and High Density (HD) imagers with high-visibility laser or green LED aimer. All imagers have 25° angle and come equipped with Adaptus 6.0 Imaging Technology
Decode Capabilities	Reads standard 1D and 2D symbologies
Development Environment	Honeywell SDK for Windows [®] Embedded
Warranty	1 year factory warranty
Service Plans	Optional three-and five-year Service Made Simple programs offer worry-free mobile computing
Wireless Connectivity	
WWAN	Software definable Gobi 3000 (data only) 3.75G radio with five-band UMTS/HSPA+ (800/850/900/1900/2100MHz), quadband GSM/GPRS/EDGE (850/900/1800/1900MHz) and dual-band EV-DO/CDMA (800/1900) support for dual SIM card Voice and data 3.75G radio with five-band UMTS/HSPA+ (800/850/900/1900/2100MHz) and quad-band GSM/GPRS/EDGE (850/900/1800/1900MHz)
WLAN	802.11a/b/g/n, Wi-Fi™ - certified
WLAN Security	WPA, WPA2 (Personal and Enterprise), 802.11x, EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC, WMM, CWG-RF Profile, CCX v.4, WAPI
WPAN	Bluetooth® V2.1, support for enhanced data rate 2.0 Mbps & 3.0 Mbps rates class II
GPS	Integrated Assisted GPS (A-GPS) with fast position acquisition and low power consumption

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation. The Bluetooth trademarks are owned by Bluetooth SIG, Inc. U.S.A. and licensed to Honeywell International Inc.

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies



For more information:

www.honeywellaidc.com

Honeywell Scanning & Mobility

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com

Honeywell

99EX-DS Rev C 03/11 © 2011 Honeywell International Inc.

Honeywell

Dolphin 99EXhc

Mobile Computer

Purpose built for use in healthcare environments, Honeywell's Dolphin[®] 99EXhc mobile computer provides extreme durability, cutting-edge wireless technology, user-friendly ergonomics, and multi-functional data capture for healthcare professionals performing a variety of applications including point-of-care, specimen collection and inventory management.

Excellent at resisting the harmful effects of fast-drying disinfecting solutions, the Dolphin 99EXhc is equipped with disinfectant-ready housings that deliver long-term reliability, reduce cleaning time and lower repair costs when compared to devices made from traditional materials.

The productivity-enhancing Dolphin 99EXhc delivers long-lasting battery life that can stand up to the challenge of extended shifts, eliminating the need for healthcare professionals to waste precious time on battery swaps. Optimized for single-handed use, the lightweight 99EXhc minimizes user fatigue and ensures that users have a free hand to provide patient care. The offering also incorporates a 3.7 inch display that provides easy viewing of more patient data on a single screen.

The 99EXhc features the latest in wireless technology, including compatibility with the new, lightning fast 802.11n standard for quicker access to critical patient data. Additionally, healthcare professionals that provide in-home patient care can connect to hospital databases, regardless of location, through use of an integrated software-definable radio that allows on-the-fly switching between GSM and CDMA networks.

Designed with input from leading healthcare institutions, Honeywell's Dolphin 99EXhc mobile computer provides a rugged solution that enables healthcare institutions to transition from paper-based to automated processes, driving increased productivity and patient safety.



Features

- **Disinfectant-Ready Housings:** Optimal for environments where the device must be cleaned frequently with harsh chemicals, and device reliability and longevity are important
- **Superior Durability:** Incorporates an IP67-rated design that withstands multiple 6 foot drops to concrete and 2,000 1 meter tumbles, resulting in a lower total cost of ownership for healthcare institutions
- Adaptus[®] Imaging Technology 6.0: Enables multifunctional data capture by providing fast scanning of linear and 2D bar codes on patient wristbands, medications and medical equipment with excellent motion tolerance, as well as seamless image capture through use of an integrated color camera
- Fast and Reliable Wireless Connectivity: Delivers full wireless coverage for hospital- and home-based healthcare professionals, allowing real-time access to critical patient data
- Optimal Combination of Performance and Usability: Improves ease of use and worker efficiency with a large screen, multiple keypad options, a super fast CPU and smart sensors
- Optional Remote MasterMind[®] Software Package: Extends mobile workforce capabilities and reduces total cost of ownership by providing a turnkey remote device management solution
- Optional Service Made Simple[™] Service Plans: Offers comprehensive, hassle-free protection on the device investment for up to five years after purchase

Dolphin 99EXhc Technical Specifications

Mechanical/Environmental	
Dimensions	8.5 [°] L x 2.7 [°] W (keypad) x 1.5 [°] (standard battery)/1.8 [°] (extended battery) 215 mm L x 69 mm W (keypad) x 39 mm (standard battery)/45mm (extended battery)
Weight	Standard battery – 505g (17.8 oz); Extended battery – 581g (20.5 oz)
Operating Temperature	-4° to 122°F (-20° to 50°C)
Storage Temperature	-13° to 158°F (-25° to 70°C)
Humidity	95% humidity, non-condensing
Drop	Withstands multiple 6' (1.8m) drops to concrete, all axis, and across operating temperature range
Tumble	Exceeds 2,000 (1m) tumbles per IEC 60068-2-32 specification
Environmental Sealing	Independently certified to meet IP67 standards for moisture and particle resistance
ESD	Air: ±15 KV; Contact: ±8 KV
System Architecture	
Processor	Texas Instruments® OMAP3715 1.0GHz processor
Operating System	Microsoft® Windows Embedded Handheld 6.5 Professional and Classic
Memory	1GB discrete NAND flash x 256 MB RAM
Display	Chemically strengthened 3.7" transflective active matrix glass display, VGA (480x640), 333 nits
Touch Panel	Industrial touch panel with resistive touch and support for finger touch and stylus
Keypad	Backlit 55-key alphanumeric, 43-key alpha shifted numeric, 34-key numeric shifted alpha (phone or calculator style)
Audio	Speaker, HAC compliant receiver, microphone
Camera	3.1 megapixel camera with Automated Camera Control (ACC). Features include automated picture profiles, camera Application Programming Interface (API), cooperational use of camera and imager, and flashlight utility
I/O Ports	RS-232/USB 2.0/audio out/charging connector, integrated IrDA port with support for SIR mode
Storage Expansion	User accessible Micro SDHC memory card slot. Please check current price guide for available qualified card options
Battery	Standard – Li-ion, 3.7V, 3060mAh; Extended – Li-ion, 3.7V, 5000mAh
Battery Life	Standard/Extended: 9 hours/15.5 hours (scanning and sending data over WLAN every 9 seconds) Standard/Extended: 8 hours/14.75 hours (scanning and sending data over WWAN every 15 seconds, GPS continuously receiving information)
Imager/Scanner	N5600/5603 Standard range (SR), Extended range (ER), and High Density (HD) imagers with high-visibility laser or green LED aimer. All imagers have 25° angle and come equipped with Adaptus 6.0 Imaging Technology
Decode Capabilities	Reads standard 1D and 2D symbologies
Development Environment	Honeywell SDK for Windows [®] Embedded
Warranty	1 year factory warranty
Service Plans	Optional three-and five-year Service Made Simple programs offer worry-free mobile computing
Wireless Connectivity	
WWAN	GSM (Voice and Data): 3.9G - HSPA+ (800/850/1900/1700/2100 MHz), GSM/GPRS/EDGE (850/900/1800/1900 MHz) Software definable Gobi 3000 (data only): 3.9G – HSPA+/UMTS (800/850/900/1700/1900/2100MHz), GSM/GPRS/ EDGE (850/900/1800/1900MHz), EVDO Rev A - 1xRTT/EVDO (800/1900 MHz); support for dual SIM card
WLAN	802.11a/b/g/n, Wi-Fi™ - certified
WLAN Security	WPA, WPA2 (Personal and Enterprise), 802.1x, EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC, WMM, CWG-RF Profile, CCX v.4, WAPI
WPAN	Bluetooth® V2.1, support for enhanced data rate 2.0 Mbps & 3.0 Mbps rates class II
GPS	Integrated Assisted GPS (A-GPS) with fast position acquisition and low power consumption

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation. The Bluetooth trademarks are owned by Bluetooth SIG, Inc. U.S.A. and licensed to Honeywell International Inc.

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies



For more information:

www.honeywellaidc.com

Honeywell Scanning & Mobility

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com



99EXhc-DS Rev B 10/11 © 2011 Honeywell International Inc.

Honeywell

Dolphin 99GX

Mobile Computer

Purpose built for transportation and logistics applications, Honeywell's Dolphin[®] 99GX mobile computer with an integrated handle provides userfriendly ergonomics, cutting-edge wireless technology, multi-functional data capture and extreme durability for front-line workers operating in a variety of locations ranging from loading docks to front line retail.

The reliable and intuitive Dolphin 99GX delivers an outstanding feature set that enables improved productivity for mobile workers. Integrated Shift-PLUS[™] technology provides all day battery life, minimizing the time and expense incurred when batteries need to be charged or replaced. The Dolphin 99GX is IP64-rated and can withstand multiple 6 feet (1.8 meters) drops to concrete, ensuring years of trouble-free operation.

The 99GX features the latest in wireless technology, including a softwaredefinable radio that allows on-the-fly switching between GSM and CDMA networks, leading to improved network coverage and lower costs related to device provisioning and deployment. Additionally, built-in Wi-Fi provides workers with access to critical data using the new, lightning fast 802.11n standard while still supporting legacy a/b/g protocols.

Integrated motion, light and proximity sensors help conserve battery life and improve ease of use by automatically optimizing the offering for the current environment. Similarly, multiple keypad options are available to ensure that the device is configured to meet diverse data input needs. With additional features such as an ultra-bright 3.7 inch display that can be read, even in direct sunlight, the Dolphin 99GX offers superior usability.

Designed with input from leading companies in the transportation and logistics sector, Honeywell's Dolphin 99GX mobile computer provides a rugged solution that increases productivity by connecting enterprises, front-line workers and customers using real-time wireless communication.



Features

- Superior Durability: Incorporates an IP64-rated design that withstands multiple 6 feet drops to concrete and 2,000 1 meter tumbles, resulting in a lower total cost of ownership for enterprises
- Shift-PLUS Power Management: Enhances productivity by providing full shift battery life, eliminating the need for employees to carry spare batteries or chargers
- Adaptus[®] Imaging Technology 6.0: Enables multifunctional data capture by providing fast scanning of linear and 2D bar codes with excellent motion tolerance, as well as seamless image capture through use of an integrated color camera
- Fast and Reliable Wireless Connectivity: Delivers full wireless coverage for applications inside and outside of the four walls, allowing real-time access to critical data
- Optimal Combination of Performance and Usability: Improves ease of use and worker efficiency with a large outdoor-viewable screen, multiple keypad options, a super fast CPU and smart sensors
- Optional Remote MasterMind[®] Software Package: Extends mobile workforce capabilities and reduces total cost of ownership by providing a turnkey remote device management solution
- Optional Service Made Simple[™] Service Plans: Offers comprehensive, hassle-free protection on the device investment for up to five years after purchase

Dolphin 99GX Technical Specifications

Mechanical/Environmental	
Dimensions	8.5″ L x 2.7″ W (keypad) x 1.5″ (standard battery)/1.8″ (extended battery) 215 mm L x 69 mm W (keypad) x 39 mm (standard battery)/45mm (extended battery)
Weight	Standard battery – 621g (21.9 oz.); Extended battery – 700g (24.7 oz.)
Operating Temperature	-4° to 122°F (-20° to 50°C)
Storage Temperature	-13° to 158°F (-25° to 70°C)
Humidity	95% humidity, non-condensing
Drop	Withstands multiple 6' (1.8m) drops to concrete, all axis, and across operating temperature range
Tumble	Up to 2,000 (1m) tumbles per IEC 60068-2-32 specification
Environmental Sealing	Independently certified to meet IP64 standards for moisture and particle resistance
ESD	Air: ±15 KV; Contact: ±8 KV
System Architecture	
Processor	Texas Instruments® OMAP3715 1.0GHz processor
Operating System	Microsoft® Windows Embedded Handheld 6.5 Professional and Classic
Memory	1GB discrete NAND flash x 256 MB RAM
Display	Chemically strengthened 3.7" transflective active matrix glass display, VGA (480x640), 333 nits
Touch Panel	Industrial touch panel with resistive touch and support for finger touch and stylus
Keypad	Backlit 55-key alphanumeric, 43-key alpha shifted numeric, 34-key numeric shifted alpha (phone or calculator style)
Audio	Speaker, microphone
I/O Ports	RS-232/USB 2.0/audio out/charging connector, integrated IrDA port with support for SIR mode
Storage Expansion	User accessible Micro SDHC memory card slot. Please check current price guide for available qualified card options
Battery	Standard – Li-ion, 3.7V, 3060mAh; Extended – Li-ion, 3.7V, 5000mAh
Battery Life	Standard/Extended: 9 hours/15.5 hours (scanning and sending data over WLAN every 9 seconds) Standard/Extended: 8 hours/14.75 hours (scanning and sending data over WWAN every 15 seconds, GPS continuously receiving information)
Imager/Scanner	N5600/5603 Standard range (SR), Extended range (ER), and High Density (HD) imagers with high-visibility laser or green LED aimer. All imagers have 25° angle and come equipped with Adaptus 6.0 Imaging Technology
Decode Capabilities	Reads standard 1D and 2D symbologies
Development Environment	Honeywell SDK for Windows [®] Embedded
Warranty	1 year factory warranty
Service Plans	Optional three-and five-year Service Made Simple programs offer worry-free mobile computing
Wireless Connectivity	
WWAN	Software definable Gobi 3000 (data only): 3.9G – HSPA+/UMTS (800/850/900/1700/1900/2100MHz), GSM/GPRS/ EDGE (850/900/1800/1900MHz), EVDO Rev A - 1xRTT/EVDO (800/1900 MHz); support for dual SIM card
WLAN	802.11a/b/g/n, Wi-Fi™ - certified
WLAN Security	WPA, WPA2 (Personal and Enterprise), 802.1x, EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC, WMM, CWG-RF Profile, CCX v.4, WAPI
WPAN	Bluetooth® V2.1, support for enhanced data rate 2.0 Mbps & 3.0 Mbps rates class II

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation. The Bluetooth trademarks are owned by Bluetooth SIG, Inc. U.S.A. and licensed to Honeywell International Inc.

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies



For more information:

www.honeywellaidc.com

Honeywell Scanning & Mobility

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com





99GX-DS Rev B 10/11 © 2011 Honeywell International Inc.